



CS520

5" 20W 100V Co-axial with Power Taps

CS630

6" 30W 100V Co-axial with Power Taps

CS520 and **CS630** are both premium co-axial ceiling speakers, both available with metal back enclosure and with adjustable power taps. Suitable for the need of quality sound production, both in BGM and Paging.

Packing Information

CS520 Carton size - 510 (L) x 500 (W) x 420 (H) mm
Gross weight - 15 kg
8 units per carton

CS630 Carton size - 570 (L) x 560 (W) x 430 (H) mm
Gross weight - 23.30 kg
8 units per carton

CS620

6" 20W 100V Co-axial

CS840

8" 40W 100V Co-axial

CS620 and **CS840** are available in 6" and 8" fixed power ratings, offering more economical co-axial ceiling types while able to deliver satisfactory sound productions, both in Paging and BGM. Back enclosure is made of ABS.

Packing Information

CS620 Carton size - 540 (L) x 540 (W) x 375 (H) mm
Gross weight - 23 kg
8 units per carton

CS840 Carton size - 630 (L) x 630 (W) x 390 (H) mm
Gross weight - 21.4 kg
8 units per carton



CS518

5" 20W 100V Co-axial with Power Taps

CS518 matches other fittings at ceiling when all others are in square or rectangular shapes and thus blends nicely with exceptional sound reproduction. Suitable for boutiques, residences, offices etc.

Packing Information

Carton size - 580 (L) x 310 (W) x 510 (H) mm
Gross weight : 17 kg
8 units per carton

Technical Specifications

	CS520	CS630	CS620	CS840	CS518
Power rating	20W 100V	30W 100V	20W 100V	40W 100V	20W 100V
Diameter	5" (125 mm)	6.5" (165 mm)	6.5" (165 mm)	8" (200 mm)	5" (125 mm)
Cone type	Co-axial with 1" tweeter				
Driver impedance	8 Ohm				
Frequency response	100 ~ 18 KHz	75 ~ 18 KHz	80 ~ 18 KHz	90 ~ 19 KHz	100 ~ 18 KHz
Sensitivity @ 1 KHz/ W / m	86 dB	88 dB	88 dB	90 dB	85 dB
Max SPL at rated output	99 dB	102 dB	101 dB	106 dB	98 dB
Power taps (100V line)	2.5 / 5 / 10 / 20W	3.8 / 7.5 / 15 / 30W	20W 100V	40W 100V	2.5 / 5 / 10 / 20W
Primary impedance (Ohm)	4k / 2k / 1k / 500	2.6k / 1.3k / 667 / 334	500	250	4k / 2k / 1k / 500
Secondary impedance	8 Ohm				
Grille / enclosure	Aluminium / Metal		Metal / ABS		Metal / Metal
Cutting hole diameter	170 mm	185 mm	205 mm	240 mm	150 x 150 mm
Dimensions (diameter x height)	205 x 145 mm	230 x 150 mm	240 x 142 mm	280 x 142 mm	180 x 180 x 135 mm
Net weight	1.70 kg	2.15 kg	2.40 kg	2.10 kg	1.80 kg
Colour	White				

