

Introduction

CS606 is a fully metal version of ceiling speaker with 6" dual cone driver. It has 1.5 / 3 / 6 W transformer taps to suit installation requirement.

Mounting is through spring clamp and the back metal enclosure fulfills the requirement of fire resistance of dome.

It is suitable for Speech and soft background music playback in areas such as :

- Hotel corridors / lobbies
- Offices
- Shopping centres for general paging and pipe in music
- Public areas



Guide to Installation

1 Cut the ceiling hole

165 mm

Ceiling

Cut the ceiling using the template with 165 mm diameter

2 Connect cable

connector

Flexible conduit 20mm Ø

Speaker cable

cut off unused cable

Connect the incoming speaker cable to the cables from the speaker according to the required power rating, as:-

- Red: 6W
- Yellow: 3W
- White: 1.5W
- Black: COM

Cut off the loose cable's conductor to avoid shorting or tape them with insulation tape.

4 Flip spring clips

Spring Clip

Spring Clip

Push upwards

Push upwards

Flip the spring clips fully upwards

3 Slot the conduit

Conduit

Slot

Upon completion of cable termination, the connector can be inserted inside the conduit, and thereafter slot in the conduit into the speaker hole at the back enclosure. The overall installation would look neat.

5 Insert speaker to ceiling hole

Fully push up clamp upwards

Ceiling

Ceiling

1

2

↑↑↑

Slot the speaker into the cut hole in slant position initially by the first spring ①, and thereafter the second spring ②

6 Installation complete

Ceiling

Ceiling

Flat and sharp screw driver

The installation is complete as shown. If it is required to uninstall the speaker, use a flat screw driver to pull it down the speakers edge.

Please do it carefully as not to damage the ceiling.