



**PM1010**  
Desktop Paging Mic



**PM1030**  
Desktop Paging Mic with Chime

**PM1010** is a basic version with simple press to talk without chime whereas **PM1030** comes with pre-announcement chime, paging contact and chime volume controls, which is designed for commercial applications. Both models had been tuned to perform better than its predecessors and shall be the right choice for your paging needs.

- **Contemporary** design
- **Dry contact** available for PM1030
- **Illuminated LED** ring gooseneck microphone
- **Line** level output, suitable for most mixing amps
- 4 tone **chime** for PM1030
- Adjustable **volume controls** for chime and microphone

**Technical Specifications**

	<b>PM1010</b>	<b>PM1030</b>
Operating voltage	24V DC	
Power consumption	0.8 W	1.3 W
Indicators	Active & Gooseneck mic ring LED	Power, Active, Gooseneck mic ring LED
Microphone system	Condenser microphone, cardioid	
Dry contact	-	3A max
Audio		
Mic sensitivity	-72 dB Omni directional	
Output impedance	Line: 300 Ohm , Mic: 50 Ohm	
Frequency response	200 Hz - 11 KHz (+/- 3 dB)	
S/N ratio	80 dB +/- 10% @ 1 KHz	
THD + Noise	<0.2%	<0.1%
Output controls	Mic	Chime, Mic
Audio output	Line output; 1.2V rms balanced , Mic: 70 mV rms balanced	
Communication		
Cable	2 m RJ45 connection at external box	
Output connection	5 way connector at external box	
Gooseneck mic length	370mm	
Dimensions (W x H x D)	160 x 50 x 120 mm (excluding mic)	
Weight	380 g	400 g

**Packing Information**

Carton size : 465 (L) x 240 (W) x 85 (H) mm  
 Gross weight : PM1010 - 1.40 kg (adaptor included)  
 : PM1030 - 1.45 kg (adaptor included)  
 1 unit per carton